


参数	位号	封装	数量
贴片电容			
104/100nF/0.1uF	C6, C7, C8, C17, C25, C26, C27, C28, C29, C31, C44, C47	0805_C	12
贴片电阻			
0R	L31	0805_R	1
750R	R9, R15, R17, R22	0805_R	4
330R	R10, R14, R18, R23	0805_R	4
680R	R11, R13, R19, R21	0805_R	4
100R	R12, R20	0805_R	2
10K	R16	0805_R	1
贴片IC			
PCM1794A	U4	SSOP-28	1
78M05	U10	TO-252-2	1
AMS1117-3.3	U11	SOT-223	1
直插元件			
2200pF/222/2.2nF	C9, C10, C11, C12, C19, C22, C23,	FKP-2	8
100uF/25V	C13, C16, C21, C30, C46	CAP-E8mm	5
104/100nF/0.1uF	C14, C20	MKS2	2
47uF/25V	C15, C18	CAP-E8mm	2
3P接线柱5.0间距	P1, P5	KF301-3P	2
2P接线柱5.0间距	P2	KF301-2P	1
6P排针2.54脚距	P4	HDR1X6	1
1位3脚RCA	P6, P7	RCA-3	2
1*3排针/2*3排针2.54脚	P8, P9, P10, P11	HDR1X3	4
OPA2604双运放	U2, U5	DIP-8	2
NE5534单运放	U3, U6	DIP-8	2

日期: 2025-04-16

温馨提示	
1位3脚RCA参考图片	
1*3排针/2*3排针2.54脚	深圳市国致电子销售部
直插电解电容为8mm直径	建议用2个2*3的排针这样好焊接
47uF容量建议47uF-100uF, 100uF可以适当增大到220/330uF	